
ALTR
S1360
RS232
AUDIO AMP
LINE-LEV
SPKR
LINE
KEY
PTT
OPTO ISOLATE
DSP
DSP SECTION 'FLATTENED'
AD5P-2181
FIT ONE ONLY
CODEC
PICOSTAR
MIC AF
MIC AMP
I.F. ORIGINAL BY G3XJP
SHORTENED
VERSION BY VK3PE
'MODS' BY MORJD
N-AGC
F AMP
MIXER
CO-AX
IF IN/OUT
10MHO 8 POLE FILTER (10.695MHz)
BI-DIR. AMP
DIODE MATRIX
TO LPF
BOARD
DC INPUT
DC SWITCH
PICASTAR BPF
ORGANAL (C) BY G3XJP
Ver's Combo
RF IN/OUT
LO INPUT
'COMBO' PICASTAR
COMBINED PCB'S TO FORM A PICASTAR TRANSCEIVER
ORIGINAL PCB BLOCKS BY G3XJP
INCORPORATES 'MODS' BY Bob, MORJD
PANEL BY VK3PE
Oct 24th, 2011
Vers. 'CC2' release
TOP
MONITOR
DIP SWITCH
TIMER
STAR TIMER
HEATER 8V
FIT HEATSINK
DDS
AMP
NO CABLE NEEDED
ANALOG PORT
LCD B/L
RTC OPTION
CR2032
EXT USB
PICASTAR
OPTO ENCODER
FROM PHM-PCB
HEATER


REFER TO: WWW.CARNUT.INFO FOR DETAILS
TWN SHLD-AUDIO CABLE
(CAN RUN VIA FRONT PANEL VOLUME POT. IF REQUIRED)
SHLD GND
SHIELDED WIRE
CO-AX CABLE
SHLD GND
CO-AX CABLE
F602
CAN FIT FILTER ON BOTTOM
CAUTION !
DO NOT SHORT TRACKS ON TOP WITH SHIELDING
SHIELDED CABLE TO MIC SOCKET
ONE OPTO IS ON TOP
WIRE TO MIC SOCKET
KEY IN
PTT IN
DOT
DASH
C1016 FITS ACROSS POINTS 'A' TO 'B' ON TOP
IF TRAP
TO PA
FROM C/O RELAY
DC INPUT
SWITCHED DC
RELAY ON TOP OR BOTTOM
PWR-SW
FAN (optn)
NOM.12V
PA DISABLE
REFER TO WEB
CO-AX CABLE
SHLD GND
LO OUT
CO-AX CABLE
SHLD GND
CO-AX CABLE
TO DRIVE SWITCH CORE SHIELD
ADDRESS SETTING
OPTIONAL FITTIN
RTC OPTION
(XTAL1)
(SEE NOTE5)
PWR SW.
BOTTOM
DSP DATA
DATA FROM PnM
DATA TO PnM
SLIDE SW FRONT
INT. SPKR
AF AMP IN
R-IN
L-IN
SHLD GND
GND
ONE OPTO IS ON TOP
OPTO2000
LM4940TS or LM4950TS
FIT ON TOP REGULATOR
CUT NOTCH IN SHIELD !
be careful with shields not to short active sections
ALTERNATE TO CROSS OVER TOP
SHIELDED CABLES !